

Connect the Printer Server

1. Connect the print server to the parallel port on the back of the printer.
2. Connect the print server to your ethernet network using an appropriate cat 5 cable (straight thru connection).
3. Connect the print server to your electricity supply using the supplied transformer.

Install the Software

4. Select one computer on your network to act as the printer administrator and install the Netgear server software (supplied on accompanying cd):
 - a) Insert the PS101 Printer Server Resource CD the CD-ROM drive. If the software does not run automatically, click on Start / Run (Windows Desktop) then type D:/Setup.exe and click [Ok] (assuming D: is your CD-ROM drive).
 - b) Follow the on-screen instructions to install the software, selecting all the components.

Configure the Printer Server

1. Click on Start / Programs / NETGEAR Print Server / NETGEAR Print Server Setup Wizard (Windows Desktop).
2. Click on [Next] in the introduction screen.
3. The next screen will show a list of Netgear printer servers connected to your network. Select the new device ("Default Server Name") and click [Next].
4.
 - a) Enter a name that will allow you to recognise the device, eg. "LabelPrinter" (NB: no spaces).
 - b) Select a workgroup that is to be allowed access to this printer.
 - c) Click [Next].
5. If your network is DHCP enabled you can leave 'Obtain IP Address Automatically' ticked and proceed to the next stage (click [Next]). Otherwise, click on 'Fixed' IP address and enter a free IP address to assign to this device as well as your network's subnet mask and default gateway addresses then click [Next].
NB: Even where DHCP is enabled, we recommend using a fixed IP address as being the more trouble free method of operation (but ensure you use an IP address outside of your network's DHCP range).
6. Click on [Finish]

Install/Connect the Printer Driver to the Printer Server

7. Click on Start / Programs / NETGEAR Print Server / NETGEAR Add Printer Wizard (Windows Desktop). Click [OK].
8. On the next screen, select the name you chose for your device then select Port 1 and click [Add].
9. Answer [No] to 'Epson Colour Stylus'.
10. If the driver for your printer is not yet installed then follow the instructions to install the driver. Go to 17.
11. If the driver is already installed then close the Add Printer wizard and continue as follows:
12. Open the printer driver – go to Start / Settings / Printers, right click on the icon for your printer and select 'Properties'.
13. Click on the 'Ports' tab.
14. Select the port entitled '{YourDeviceName}_P1' (tick the box on the left).
15. Click [Apply].
16. Click on the General Tab then [Print Test Page] a test sample should be sent to your printer.
17. Printer Server is installed.

If you wish to print to your device from more than one computer, install the NETGEAR Add Printer Wizard **only** on each additional computer then perform steps 7-17 above.